

resistant material. Manifold burst panel(s) meeting SFI Spec 23.1 mandatory. If single panel is used, total area of rupture disk must equal or exceed 10 square inches. If multiple panels are used, total area of rupture disks must equal or exceed 12 square inches. Panels may be installed in the front and back, or on each side, of manifold. Only one panel per opening permitted. "Doubling" or "tandem" panel installations prohibited. See General Regulations 1:10, 1:11.

SECTION 17:FUNNY CAR, FRAME:4, PARACHUTE (Page 6)

Dual parachutes mandatory. Two separate shroud line mounting points mandatory with sleeved 1/2-inch-minimum Grade 8 steel bolts with self-locking nuts or with nuts welded onto parachute brackets. Shroud line mounting brackets must be constructed of minimum 3/16-inch 4130 steel or titanium. Shroud lines must be covered with 1/16-inch-thick leather or NHRA-accepted material from mounting point into the pack. Two NHRA-accepted parachute tethers are required and must be routed through each shroud line end loop and be attached using the rear end mounting bolt(s) on each side. The mounting attachments on each end of both tethers must attach to either separate rear end mounting bolts or opposite ends of a single bolt (one under the head of the bolt and the other under the nut). ~~Tethers must be covered with a fire-resistant material.~~ NHRA-accepted parachute tethers: Amick Race Car Restraints ~~part number~~ PARA-101REV1, Future Fibres FF30MLB-P-MB or Taylor Motorsports 108. When Future Fibres FF30MLB-P-MB is used only one tether is required and must be routed through each shroud line end loop and be attached using the rear end mounting bolt on each side. All tethers must be covered with a fire-resistant material. Two separate release cables mandatory. Parachute mounting box must be NHRA- accepted prior to competition. The parachute floor must be flat and may not extend more than 6 inches rearward or beyond the parachute pack, whichever is less. The measurement will be taken from the mounting point on the rear of the body. The use of a wicker prohibited. See General Regulations 4:8.

SECTION 17:FUNNY CAR, SUPPORT GROUP:9, ~~ACCIDENT DATA RECORDER~~ (Page 12)

~~Properly installed and operational Ford Accident Data Recorder (part number MS0148) required. The Ford Accident Data Recorder must be installed per the manufacturer's instructions. Modification of or tampering with the Ford Accident Data Recorder prohibited.~~

SECTION 17: FUNNY CAR, SUPPORT GROUP:9, EVENT DATA RECORDER (Page 12)

Properly installed and operational PRC Systems Event Data Recorder (part number EDR1.0) and PRC Systems Wire Assembly (part number WA1.0) mandatory. The PRC Systems Event Data Recorder and Wire Assembly must be installed per the manufacturer's instructions. Modification of or tampering with the PRC Event Data Recorder and Wire Assembly prohibited.